

DO NOT ENTER - PROPOSED AMENDMENT for interview purpose BK 12/23/2008**Krasnic, Bernard**

From: Purohit, Ameya [apurohit@HDP.com]
Sent: Tuesday, December 23, 2008 3:26 PM
To: Krasnic, Bernard
Subject: U.S. Patent Application 10/699,922
Attachments: 2008-12-23 Claim Amendments re Examiner Suggestions_v2.doc

Dear Sir:

As discussed and agreed, attached are proposed amendments to claims 1 and 32 to put the present Application in condition for allowance.

In view of the proposed claim amendments, withdrawal of the election of species requirement and a rejoinder of the withdrawn claims is respectfully requested since the withdrawn claims are now dependent on allowable generic claims.

Should there be any matters that need to be resolved in the present application; the Examiner is respectfully requested to contact Ameya Purohit at the telephone number below.

<<2008-12-23 Claim Amendments re Examiner Suggestions_v2.doc>>

Amyea Purohit on behalf of John A. Castellano (Reg # 35,094)
Harness, Dickey & Pierce, P.L.C.
(703) 668-8048

***** ATTENTION *****
This message is confidential and intended only for the individual to whom or entity to which it is addressed. This message may contain information that is protected by the attorney/client privilege. If you are not the intended recipient or addressee, or an employee or agent responsible for delivering this message to the addressee, you are hereby notified that any dissemination, distribution, or copying, in whole or part, of this message is strictly prohibited. If you believe that you have been sent this message in error, please do not read it. Please immediately reply to sender that you have received this message in error. Then permanently delete all copies of the message. Thank you.

HDP LEGAL NOTICE: The information contained in this transmission is intended only for the individual(s) or entity(ies) to whom it is addressed. It may contain information protected from use and/or disclosure by law, including information that is privileged or confidential attorney-client privileged, attorney work product and/or trade secrets. If the reader of this message is not the intended recipient, or an employee or agent responsible for delivering this message to the addressee, the reader is hereby notified that any use, distribution or copying of this communication is strictly prohibited. If you believe you have received the facsimile or message in error, please immediately recall us at our expense by return mail or e-mail and permanently delete or destroy all copies of the message.
To comply with U.S. Treasury regulations, we advise you that any discussion of Federal tax issues in this communication will not be intended to be used, and cannot be used, by any person (i) to avoid penalties that may be imposed by the Internal Revenue Service, or (ii) to promote, market or recommend to another party any matter addressed herein.

DO NOT ENTER - PROPOSED AMENDMENT for interview purpose BK 12/23/2008

Any portions of this transmission containing controlled technical data are restricted by U.S. export laws and regulations, and may not be distributed or retransmitted to non-U.S. persons without appropriate licensing or a licensing exception. Neither this information block nor the typed name of the sender, nor anything else in this message is intended to constitute an electronic signature unless a specific statement to the contrary is included.

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application No.: 10/699,922 Group Art Unit: 2624

Filing Date: November 4, 2003 Examiner: Krasnic, Bernard

Applicant: Hyun-Sang PARK

Title: IMAGE PROCESSING APPARATUS AND METHOD FOR
CONVERTING IMAGE DATA BETWEEN RASTER SCAN
ORDER AND BLOCK SCAN ORDER

Attorney Docket: 8947-000064/US

AMENDMENTS TO THE CLAIMS

The following is a complete, marked-up listing of revised claims with a status identifier in parenthesis, underlined text indicating insertions, and strike through and/or double-bracketed text indicating deletions.

LISTING OF CLAIMS

1. (Currently Amended) An image processing apparatus for converting image data between a raster scan order and a block scan order, comprising:

an image data processor for supplying image data of a raster scan order having a given horizontal resolution and a given vertical resolution;

a line memory for storing image data of a plurality of lines;

an address generating block for converting supplied image data of raster scan order to block scan order by generating a common read/write address for the line memory so that only one line memory is required for performing simultaneous read and write operations, the address generating block including

a block address generator for generating an address of a block which image data is read from and written into;

a line offset generator for providing a line offset between an earlier common read/write address and a present common read/write address for the line memory; and an address generator including

a multiplexer sequentially providing a plurality of input values including at least one output of at least two adders and the address of the block to a next anchor address register;

a first adder of the at least two adders outputting a sum of a next anchor address of the next anchor address register and the line offset;

a second adder of the at least two adders outputting a difference of the next anchor address of the next anchor address register and a desired value;

an anchor address register receiving the next anchor address from the next anchor address register; and

a common read/write address operator operating upon the received next anchor address to generate the common read/write address; and

an encoder receiving image data of the block scan order from the line memory and encoding the received image data.

Deleted: a multiplexer; a next anchor address register; a anchor address register; a common read/write address operator and at least two adders, for generating the common read/write address for the line memory based on the block address and the line offset

2. (Cancelled)

3. (Original) The apparatus of claim 1, wherein the encoder is a Joint Photographic Experts Group (JPEG) engine.

4. (Previously Presented) The apparatus of 1, wherein the block includes image data of horizontal-direction pixels and vertical-direction pixels.

5. (Previously Presented) The apparatus of claim 1, wherein the block address generator provides a block offset between a start address of a present block and a start address of a next block for the line memory.

6. (Original) The apparatus of claim 5, wherein the block offset is initially set to 1.

7. (Previously Presented) The apparatus of claim 1, wherein the line offset is initially set to a value defined by the given horizontal resolution divided by a number of horizontal-direction pixels in a given block.

8. (Previously Presented) The apparatus of claim 1, wherein the line offset generator generates a next line offset between a present common read/write address and a next common read/write address for the line memory.

9. (Original) The apparatus of claim 8, wherein the block address and the next line offset are respectively reset at a start of every phase.

10. (Previously Presented) The apparatus of claim 1, wherein the address generator generates an anchor address for the line memory based on the block address, and generates a sequential number of the common read/write address from the generated anchor address.

11. (Original) The apparatus of claim 10, wherein the address generator increases the anchor address to equal the line offset after the address generator generates the sequential number of the common read/write address.

12. (Original) The apparatus of claim 10, wherein the address generator decreases the anchor address to the given horizontal resolution minus one (H-1) when the anchor address has increased so as to equal or exceed (H-1).

13. (Original) The apparatus of claim 5, wherein the block address generator increases the block address as much as the block offset after the block address generator generates the common read/write addresses for a block.

14. (Previously Presented) The apparatus of claim 1, wherein the block address generator decreases the block address to the given horizontal resolution minus one (H-1) when the block address has increased so as to equal or exceed (H-1).

15. (Original) The apparatus of claim 5, wherein the block offset is set to the line offset at an end of every phase.

16. (Original) The apparatus of claim 8, wherein the line offset is set to the next line offset at an end of every phase.

17. (Previously Presented) The apparatus of claim 16, wherein a phase comprises a number of blocks equal to the given horizontal resolution divided by a number of horizontal-direction pixels in a given block.

18. (Original) The apparatus of claim 15, wherein image data having the given horizontal resolution (H) and the vertical resolution (V) comprises V/v phases, wherein v represents a number of vertical-direction pixels in a given block.

19. (Previously Presented) The method of claim 32 wherein generating the common read/write address further comprises:

- (a) initializing a block offset and a line offset;
- (b) initializing a block address and a next line offset;
- (c) setting an anchor address to the block address;
- (d) generating a sequential number of common read/write addresses from the anchor address;
- (e) increasing the anchor address as much as the line offset;
- (f) repeating (d)~(e) until the common read/write addresses for all blocks are generated;
- (g) increasing the block address as much as the block offset;
- (h) increasing the next line offset as much as the line offset;
- (i) repeating (c)~(h) until image data for a number of blocks equal to the given horizontal resolution divided by a number of horizontal-direction pixels in a given block are processed;
- (j) setting the block offset to the line offset;
- (k) setting the line offset to the next line offset;

(l) repeating (b)~(k) during a time when image data of the raster scan order is supplied.

20. (Previously Presented) The method of claim 19, wherein (e) includes reducing the anchor address so as to equal the horizontal resolution, when the anchor address increase equals or exceeds the horizontal resolution.

21. (Previously Presented) The method of claim 19, wherein (h) includes reducing the block address so as to equal the horizontal resolution, when the block address increase equals or exceeds the horizontal resolution.

22. (Withdrawn) The method of claim 32 wherein generating the common read/write address further comprises:

- (a) initializing a block offset and a line offset;
- (b) generating an anchor address as a function of the block offset, line offset and horizontal resolution;
- (c) generating a sequential number of common read/write addresses as a function of the anchor address and a number of horizontal-direction pixels in a given block;
- (d) repeating (b)~(c) until the common read/write addresses for all blocks are generated;
- (e) repeating (b)~(c) until a block sequence of image data (i) for the plurality of lines (v) has sequentially increased from 0 to v-1;
- (f) setting the block offset to the line offset;
- (g) setting a remnant obtained as a function of the line offset and horizontal resolution to the line offset; and

(h) repeating (b)~(g) during a time when image data of the raster scan order is supplied.

23. (Withdrawn) The method of claim 32 wherein generating the common read/write address further comprises:

- (a) initializing a block offset and a line offset;
- (b) initializing a block address;
- (c) initializing a line address;
- (d) generating an anchor address as a function of the block address, line address and horizontal resolution;
- (e) generating a sequential number of common read/write addresses as a function of the anchor address and a number of horizontal-direction pixels in a given block;
- (f) increasing the line address as much as the line offset;
- (g) repeating (d)~(f) until the common read/write addresses for all blocks are generated;
- (h) increasing the block address as much as the block offset;
- (i) repeating (c)~(h) until image data for a number of blocks equal to the horizontal resolution divided by the number of horizontal-direction pixels in a given block are processed;
- (j) setting the block offset to the line offset;
- (k) setting a remnant obtained as a function of the line offset, horizontal resolution and number of horizontal-direction pixels in a given block to the line offset; and
- (l) repeating (b)~(k) during a time when image data of the raster scan order is supplied.

24. (Withdrawn) The method of claim 32 wherein generating the common read/write address further comprises:

- (a) initializing a block offset and a line offset;
- (b) initializing a block address;
- (c) initializing a line address;
- (d) generating an anchor address based on the block address and the line address;
- (e) generating a sequential number of common read/write addresses as a function of

the anchor address and a number of horizontal-direction pixels in a given block;

(f) increasing the line address as much as the line offset;
(g) repeating (d)~(f) until the common read/write addresses for all blocks are generated;

(h) increasing the block address as much as the block offset;
(i) repeating (c)~(h) until image data for a number of blocks equal to the horizontal resolution divided by the number of horizontal-direction pixels in a given block (H/h) are processed;
(j) setting the block offset to the line offset;
(k) setting the line offset * H/h to the line offset; and
(l) repeating (b)~(k) during the time when image data of the raster scan order is supplied.

25. (Withdrawn) The method of claim 24, wherein (d) includes reducing the anchor address so as to substantially equal the horizontal resolution, when the anchor address increase equals or exceeds the horizontal resolution.

26. (Withdrawn) The method of claim 24, wherein (f) includes reducing the line address so as to be substantially equal the horizontal resolution, when the line address increase equals or exceeds the horizontal resolution.

27. (Withdrawn) The method of claim 24, wherein (h) includes reducing the block address so as to be substantially equal to the horizontal resolution, when the block address increase equals or exceeds the horizontal resolution.

28. (Withdrawn) The method of claim 24, wherein (k) includes setting the remnant to the line offset, when the set line offset equals or exceeds the horizontal resolution.

29. (Withdrawn) The method of claim 32 wherein generating the common read/write address further comprises:

- (a) initializing a block offset and a line offset;
- (b) initializing a block address;
- (c) setting an anchor address to the block address;
- (d) generating a sequential number of common read/write addresses as a function of the anchor address and a number of horizontal-direction pixels in a given block;
- (e) increasing the anchor address as much as the line offset;
- (f) repeating (d)~(e) until the common read/write addresses for $h*v$ blocks are all generated;
- (g) increasing the block address as much as the block offset;
- (h) repeating (c)~(g) until image data for a number of blocks equal to the horizontal resolution divided by the number of horizontal-direction pixels in a given block (H/h) are processed;

- (i) setting the block offset to the line offset;
- (j) setting a remnant obtained as a function of the line offset, H/h and horizontal resolution to the line offset; and
- (k) repeating (b)~(j) during a time when image data of the raster scan order is supplied.

30. (Withdrawn) The method of claim 29, wherein (c) includes reducing the anchor address so as to substantially equal the horizontal resolution, when the anchor address increase equals or exceeds the horizontal resolution.

31. (Withdrawn) The method of claim 29, wherein (g) further includes reducing the block address so as to be substantially equal to the horizontal resolution, when the block address increase equals or exceeds the horizontal resolution.

32. (Currently Amended) A method for converting image data between a raster scan order and a block scan order, comprising

receiving image data of a raster scan order having a given horizontal resolution and a given vertical resolution;

generating a common read/write address for a line memory of a plurality of lines for performing simultaneous read and write operations using an address generator having

a multiplexer sequentially providing a plurality of input values including at least one output of at least two adders and an address of a block to a next anchor address register;

a first adder of the at least two adders outputting a sum of a next anchor address of the next anchor address register and a line offset;

a second adder of the at least two adders outputting a difference of the next anchor address of the next anchor address register and a desired value;

an anchor address register receiving the next anchor address from the next anchor address register; and

a common read/write address operator operating upon the received next anchor address to generate the common read/write address;

reading image data of a block scan order from the common read/write address of the line memory;

storing image data of the raster scan order in the common read/write address of the line memory;

converting stored image data of raster scan order to the block scan order; and

transmitting image data of the block scan order to an encoder, the encoder encoding the received image data.

Deleted: a multiplexer, a next anchor address register, a anchor address register, a common read/write address operator and at least two adders

33. (Previously Presented) The method of claim 32, wherein generating the common read/write address is based in part on generating an anchor address, the anchor address representing a segment of pixels of image data that is read from and written to the line memory.

34. (Original) The method of claim 33, wherein the anchor address is generated based on at least one of a block address of a block, of the block scan order, in which image data is read from and written to in the line memory, and a block offset between a start address of a present block and a start address of a next block for the line memory.

35. (Original) The method of claim 34, wherein the anchor address is set based only on the block address.

36. (Previously Presented) The method of claim 35, wherein generating a common read/write address further comprises:

- (a) initializing the block offset and a line offset;
- (b) initializing the block address and a next line offset;
- (c) setting the anchor address to the block address;
- (d) generating a sequential number of common read/write addresses from the anchor address;
- (e) increasing the anchor address as much as the line offset;
- (f) repeating (d)~(e) until the common read/write addresses for all blocks are generated;
- (g) increasing the block address as much as the block offset;
- (h) increasing the next line offset as much as the line offset;
- (i) repeating (c)~(h) until image data for a number of blocks equal to the given horizontal resolution divided by a number of horizontal-direction pixels in a given block are processed;
- (j) setting the block offset to the line offset;
- (k) setting the line offset to the next line offset;
- (l) repeating (b)~(k) during a time when image data of the raster scan order is supplied.

37. (Withdrawn) The method of claim 35, wherein generating a common read/write address further comprises:

- (a) initializing the block offset and a line offset;
- (b) initializing the block address;
- (c) setting the anchor address to the block address;
- (d) generating a sequential number of common read/write addresses as a function of the anchor address and a number of horizontal-direction pixels in a given block;
- (e) increasing the anchor address as much as the line offset;
- (f) repeating (d)~(e) until the common read/write addresses for $h \times v$ blocks are all generated;
- (g) increasing the block address as much as the block offset;
- (h) repeating (c)~(g) until image data for a number of blocks equal to the horizontal resolution divided by the number of horizontal-direction pixels in a given block (H/h) are processed;
- (i) setting the block offset to the line offset;
- (j) setting a remnant obtained as a function of the line offset, H/h and horizontal resolution to the line offset; and
- (k) repeating (b)~(j) during a time when image data of the raster scan order is supplied.

38. (Withdrawn) The method of claim 34, wherein the anchor address is generated based on the block offset, a line offset between an earlier common read/write address and a present common read/write address for the line memory, and the horizontal resolution.

39. (Withdrawn) The method of claim 38, wherein generating a common read/write address further comprises:

- (a) initializing the block offset and the line offset;
- (b) generating the anchor address as a function of the block offset, line offset and horizontal resolution;
- (c) generating a sequential number of common read/write addresses as a function of the anchor address and a number of horizontal-direction pixels in a given block;
- (d) repeating (b)~(c) until the common read/write addresses for all blocks are generated;
- (e) repeating (b)~(c) until a block sequence of image data (i) for the plurality of lines (v) has sequentially increased from 0 to v-1;
- (f) setting the block offset to the line offset;
- (g) setting a remnant obtained as a function of the line offset and horizontal resolution to the line offset; and
- (h) repeating (b)~(g) during a time when image data of the raster scan order is supplied.

40. (Withdrawn) The method of claim 34, wherein the anchor address is generated based on at least the block address and a line address

41. (Withdrawn) The method of claim 40, wherein generating a common read/write address further comprises:

- (a) initializing the block offset and a line offset;
- (b) initializing the block address;
- (c) initializing the line address;

- (d) generating the anchor address as a function of the block address, line address and horizontal resolution;
- (e) generating a sequential number of common read/write addresses as a function of the anchor address and a number of horizontal-direction pixels in a given block;
- (f) increasing the line address as much as the line offset;
- (g) repeating (d)~(f) until the common read/write addresses for all blocks are generated;
- (h) increasing the block address as much as the block offset;
- (i) repeating (c)~(h) until image data for a number of blocks equal to the horizontal resolution divided by the number of horizontal-direction pixels in a given block are processed;
- (j) setting the block offset to the line offset;
- (k) setting a remnant obtained as a function of the line offset, horizontal resolution and number of horizontal-direction pixels in a given block to the line offset; and
- (l) repeating (b)~(k) during a time when image data of the raster scan order is supplied.

42. (Withdrawn) The method of claim 40, wherein generating a common read/write address further comprises:
- (a) initializing the block offset and a line offset;
 - (b) initializing the block address;
 - (c) initializing the line address;
 - (d) generating the anchor address based on the block address and the line address;
 - (e) generating a sequential number of common read/write addresses as a function of the anchor address and a number of horizontal-direction pixels in a given block;

- (f) increasing the line address as much as the line offset;
- (g) repeating (d)~(f) until the common read/write addresses for all blocks are generated;
- (h) increasing the block address as much as the block offset;
- (i) repeating (c)~(h) until image data for a number of blocks equal to the horizontal resolution divided by the number of horizontal-direction pixels in a given block (H/h) are processed;
- (j) setting the block offset to the line offset;
- (k) setting the line offset * H/h to the line offset; and
- (l) repeating (b)~(k) during the time when image data of the raster scan order is supplied.

43. (Original) An image processing apparatus for converting image data between a raster scan order and a block scan order in accordance with the method of claim 19.

44. (Withdrawn) An image processing apparatus for converting image data between a raster scan order and a block scan order in accordance with the method of claim 22.

45. (Withdrawn) An image processing apparatus for converting image data between a raster scan order and a block scan order in accordance with the method of claim 23.

Application No. 10/699,922
Attorney Docket No. 8947-000064/US

46. (Withdrawn) An image processing apparatus for converting image data between a raster scan order and a block scan order in accordance with the method of claim 24.

47. (Withdrawn) An image processing apparatus for converting image data between a raster scan order and a block scan order in accordance with the method of claim 29.

48. (Original) An image processing apparatus for converting image data between a raster scan order and a block scan order in accordance with the method of claim 32.

49. (Cancelled)

*** END CLAIM LISTING ***